

Compliance Made Easy

ProExtender

The ProExtender increases the range of the ProHubs dedicated wireless network, allowing you to connect pro hardware devices over a greater distance.




Overview

ProExtender is ideal for areas where the signal path may be interrupted or for installing Pro Range devices a long distance from ProHub.

Features


- Connects up to 500 Pro Range devices
 - Extends range by 40-50m (site specific)
- Available in POE and 24V

ProExtender Midi



Dimensions	240 mm (w) x 260 mm (h) x 55 mm (d)
Weight	920 g
Power	Power-over-Ethernet
Part number	700-9825

ProExtender Maxi



Dimensions	245 mm (w) x 325 mm (h) x 90 mm (d)
Weight	2090 g
Power	Mains powered with (optional) battery backup
Part number	550-7411

Contact our team for more information

Call: 01273 320650
Email: contact@fireco.uk
Web: www.fireco.uk

Specification Overview

Colour	Grey cover / black base
Installation position	Wall-mounted
Usage	Extended Pro radio network
Maximum number of connected units	50 ProExtenders and 500 Dorgard Pro
Radio frequency	433-434 MHz
Range	Typically 40-50m (site specific)
Compliant to	EMC Directive, Radio Equipment Directive, CE Marked
Suitable for	Can form part of a Critical (category A) installation under BS7273-4 2015

Expand the system

The ProExtender can be used as part of an expandable system. See below for compatible products

Dorgard Pro	360-1551 Dorgard Pro Black 956-8278 Dorgard Pro White
Freedor Pro	338-0604 Freedor Pro Silver Finish 170-2053 Freedor Pro Brass Finish
ProHub ProExtender is designed to be used in conjunction with the ProHub	198-1593 ProHub Midi 649-4204 ProHub Maxi