

Hush-Pro Landlord System Interface (CAST Protocol)

Part No. **HP733/CA**



Overview

Compatible with C-TEC's CAST protocol XFP and ZFP addressable fire panels.

Allows a stand-alone Hush-Pro domestic fire alarm system to be connected to a CAST landlord/communal system to unlock a series of powerful optional features such as remote off-site monitoring via the Cloud, automatic evacuation of dwellings in a Fire Level 2 condition, manual keyswitch evacuations by the fire and rescue services and more.

Visit our Domestic Fire Systems section for more information on Hush-Pro - a new approach to integrating domestic and communal/landlord fire alarm systems.

For availability details email hush-pro@c-tec.co.uk

Technical Specifications

| | |
|----------------------------------|---|
| Protocol/compatibility | C-TEC CAST (XFP & ZFP fire panels). |
| Power requirements | Loop powered (individual Hush-Pro Controllers/Systems are powered by their own PSUs). |
| Quiescent current | TBC. |
| Indicators | Local Fire (Fire Level 1), Global Fire (Fire Level 2), Fault (from Hush-Pro Controller) and Loop Fault. |
| Product dimensions (mm) | 146 W x 85 H x 21 D mm (Can be mounted on a standard UK 25mm double gang flush or surface back box). |
| Construction & finish | Supplied on a double gang plastic plate. |
| IP Rating | IP40. |
| Operating conditions/temperature | -5°C to +40°C. Max relative humidity: 95%. |
| Notes | More detailed tech specs to follow. |