



## CAST 96dB Compact ceiling sounder, white

Part No. **CA450A/SW**



### Overview

LPCB certified to EN54-3 & 17 and Kiwa Telefication certified to EN54-13.

Impressive 96dB(A) sound output @ 1m.

Onboard short-circuit loop isolator.

5.5mA typical alarm current (460µA quiescent current) @24-40V DC (Sounder on max).

Group addressing facility allows multiple devices to be operated simultaneously.

4 selectable volume levels and 31 selectable tones.

IP21C rated.

IP21C rated.

### More Information

CAST<sup>®</sup> is the world's most-advanced 'distributed intelligence' fire alarm system protocol. Conceived, designed and realised by C-TEC as part of a five-year, multi-million pound project, it involved the creation of a powerful proprietary communication protocol (C-TEC Addressable System Technology, CAST) and multiple control panels & field devices. Now available to purchase, its key features include:

255 devices per loop.

Autonomous decision-making for faster response times.

Multiple type codes.

40V loop drive voltage.

Two 'soft' addressing options - automatic via the panel or manual via a powerful handheld programmer.

Powerful multi-level addressing facilitates easy device addition and swapped device identification.

Multiple functionality at a single address (integrated devices) - coming soon.

Volumes, tones & detector modes can be changed at compatible panels.

High-speed data transmission and robust data transfer.

Intrinsically EN54-13 compliant.



T 01942 322744 E sales@c-tec.co.uk

F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



Provides geographical location of short and open circuit faults (a short circuit isolator is included as standard in every CAST field device).

Replace device function.

Future seamless integration with other CAST life safety systems reducing energy, servicing, installation and repair costs.

Designed and manufactured in the UK.

## Technical Specifications

|                                    |  |
|------------------------------------|--|
| Approvals/certifications           | LPCB certified to EN54-3 & 17 and Kiwa Telefication certified to EN54-13 |
| Protocol/compatibility             | Compatible with C-TEC's CAST protocol Addressable Fire Panels.           |
| Application/operation              | Suitable for ceiling or wall mounting.                                   |
| Supply/operating voltage           | 24 to 40V DC.  |
| Quiescent current                  | 460µA typical.   |
| Nominal SPL (Sound Pressure Level) | 96dB(A) when set to tone 1.  |
| Alarm current                      | 5.5mA @ 24 to 40V DC.(Sounder on max).                                   |
| Indicators                         | Polling (red LED).   |
| Product dimensions (mm)            | 102mm diameter x 63mm deep.  |
| IP Rating                          | IP21C (Type A).  |
| Weight                             | 160g.  |
| Operating conditions/temperature   | -10°C to +55°C. Max. 95% RH (Non-condensing).                            |



T 01942 322744 E sales@c-tec.co.uk

F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom